

ROLLANT		540 RC COMFORT	540 RC	540 RF
Hitching				
PTO shaft speed	rpm	540/1000	540/1000	540/1000
Wide-angle drive shaft with cam control		●	●	●
Pick-up				
Width	m	2.10	2.10	2.10
DIN pick-up width	m	1.90	1.90	1.90
Hydraulic pick-up lift		●	●	●
Ground-contour following with two height-adjustable castor guide wheels		●	●	●
Fixed guide wheels		●	●	●
Castor guide wheels		○	○	○
Folding castor guide wheels		○	○	○
Feeder system				
Rotor		ROTO CUT	ROTO CUT	ROTO FEED
Knife group changing		0, 7, 8, 15	0, 15	–
Hydraulic connection				
Single-acting spool valve for pick-up lift		●	●	●
Dual-acting spool valve for tailgate rams		–	●	●
Single-acting spool valve with free-flow return + LS		●	–	–
Bale chamber				
Number of compaction rollers		15	15	15
MAXIMUM PRESSURE SYSTEM (MPS II)		○	○	○
ROLLATEX net wrapping		–	●	●
Twine/ROLLATEX net wrapping		–	○	○
ROLLATEX COMFORT net wrapping		●	–	–
Film/ROLLATEX COMFORT net wrapping		○	–	–
Bale chamber dimensions	m	1.22 × 1.25	1.22 × 1.25	1.22 × 1.25
Operating console				
ISOBUS cable		●	●	●
OPERATOR		□	□	□
COMMUNICATOR		□	□	□

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.